



Premium+ 4000kg 400V

Two-column lift 4,5m

VL40F400B



- Floor-less / barrier-free
- Fully automatic
- Double and triple adjustable arms
- Quality hydraulic pump
- Adjustable pads with double spindle



Quality hydraulic pump



Double spindle

Height adaptor



The thoughtful design of Falco bridges saves you time and effort. The focus is on ease of use and an efficient work flow. The different models are developed for various applications. The PremiumPlus is a fully automatic and barrier-free model, making this bridge very complete and suitable for a wide range of vehicles. The Falco Sollevatori Premium series has proven itself over the years to be a very reliable and multi-purpose bridge, for almost all common cars.

Technical specifications

capacity	4000 kg
voltage	400 V 3-fase
engine power	2,2 kw
min. take-up height	95mm
maximum lifting height	2050mm
reach short lift arms	625 - 932mm
reach long lifting arms	825 - 1750mm
distance between columns	2785mm
height of the columns	2806mm
overall height	3756mm
total width	3540mm
weight	680kg
oil capacity	10L CH32 / CH46 (Niet inbegrepen)

Alle Falco vrachtwagenbruggen voldoen aan de NEN-EN1493 veiligheidsnorm en worden geleverd met een Nederlandstalige handleiding inclusief onderhoudsprotocol en CE-certificaat 2006/42/EC.

Features

- Floor-less / barrier-free
- Double and triple telescopic adjustable support arms
- Steel cable equalisation control (synchronisation)
- Quality hydraulic pump incl. cooling fins
- 24V control box
- Transparent oil reservoir incl. oil level
- Foot protection incl. acoustic safety signal
- Stop on reaching highest position
- Height-adjustable support pads with double spindles
- Standard raised support bushings
- Automatic support arm locking
- Fully automatic electric locking
- Inner column cover
- Chain guard
- Robust columns made of rolled steel
- Protection rubber door stop
- Hydraulic cylinder on both sides
- Deadman's handle for raising and lowering
- Automatic overload protection
- Height limit switch
- 12 heavy duty M18 locking bolts

